

BIODEGRADABLE LITHIUM COMPLEX #0 GREASE

Description

RSC *EnviroLogic*® Grease 0 is a multi-purpose, biodegradable Lithium Complex #0 grease. It provides excellent low temperature pumpability, antiwear performance and corrosion protection.

Specially designed for high performance in industrial applications where incidental environmental exposure of the lubricant is a cause for concern. It is biodegradable and will not cause harm to aquatic life or animals.

RSC *EnviroLogic*® Grease 0 is an Environmentally Acceptable Lubricant (EAL) compliant with 2013 US EPA Vessel General Permit (VGP).

RSC *EnviroLogic*® Greases meet the requirements for various manufacturers. Visit our [website](#) or contact customer service for a full list of OEM approvals.

Typical Properties

| | | |
|---------------------------------|------------|---------|
| NLGI Grade | | #0 |
| Worked Penetration, (mm/10) | ASTM D217 | 355-385 |
| Dropping Point, °F | ASTM D2265 | 397 |
| Four-Ball Weld, (kgf) | ASTM D2596 | 250 |
| Four-Ball Wear, mm | ASTM D2266 | 0.42 |
| Steel Corrosion | ASTM D1743 | Pass |
| Copper Corrosion | ASTM D4048 | 1b |
| Base Oil Viscosity @ 40°C, cSt. | ASTM D445 | 55 cSt |
| Color | Visual | Amber |
| Appearance | Visual | Smooth |

NOTICE: While this information is presented in good faith and believed to be accurate, RSC Bio Solutions does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and RSC Bio Solutions disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.

Updated:
12/7/2016

For more information about RSC Bio Solutions, visit us at rscbio.com or call +1 704.684.6100.